

CASING BRAND CODES

Armstrong	AR
Aurora	AU
Bridgestone	BS
Continental	CN
Cooper	CP
Dunlop	DU
Firestone	FS
General	GN
Goodrich	GR
Goodyear	GY
Kelly	KL
Kumho	KU
Michelin	MI
Ohtsu	OH
Pirelli	PI
Private Brand	PB
Semperit	SE
Sears / Allstate	SR
Sumitomo	SU
Toyo	TO
Uniroyal	UN
Yokohama	YO
Other (Explain In Comments)	OT

Bandag	BG
Goodyear	GY
Hawkinson	HW
Hercules	HL
Longmile	LM
Marangoni	MA
Michelin	MI
Mohawk	MO
Oliver	OL
Oncor	ON
Robbins	RB
Other	OT

SHEET HEADING

DESCRIPTION

Brand / Tire Tag Number	Number Used By Fleet to Identify Tire, Branded on Tire in Branding Block .
Casing Brand	Manufacturer of Casing. Use Casing Brand Codes to Abbreviate Manufacturer.
Casing Size	Size of Tire, Indicated on Sidewall of Tire.(For Low Profile Tires Use LP to Abbreviate Size. EX - LP22.5)
Casing Pattern	Tread Pattern (Name) of Casing.
Casing DOT (Plant) —	CASING DOT DOT - Y7BP3RF124 DOT - Department of Transportation Y7 - Manufacturer & Plant Code BP - BP Tire Size Code Number 3RF - Group or Optional Symbols with the Manufacturer
Casing DOT (Week) —	12 - Date of Manufacture - Week
Casing DOT (Year) —	4 - Date of Manufacture - Year
Retread Brand	Manufacturer of Retread. Use Retread Brand Codes to Abbreviate Manufacturer.
Retread Pattern	Tread Pattern of Retread.
Retread DOT (Plant) —	RETREAD DOT R BEL C1 156 R - Retread BEL - Retread Manufacturer Plant Code C1 - Chamber / Mold Number
Retread DOT (Week) —	15 - Date of Retread - Week
Retread DOT (Year) —	6 - Date of Retread - Year
Number of Retreads	Number of Times Casing Has Been Retreaded. (Indicated by Number of Retread DOT's)
Primary Removal Condition	Primary Reason Why Tire Was Removed From Service. (Removal Codes Listed On Bottom Of Front Page)
Secondary Removal Condition	Secondary Or Additional Reason Why Tire Was Removed From Service. (Use Same Codes As Primary Codes)
Number of Repairs	Number of Repairs Observed on Tire Casing.
Retreadable / Repairable	Place An "X" In Box If Tire Can Be Retreaded Or Repaired And Placed Back Into Service.
Warrantable	Place An "X" In Box If Tire Is Warrantable By Casing Manufacturer, Retread Manufacturer Or Repairing Facility.
Responsibility	Enter One Of The Following: U - User Related Removal. M - Casing Manufacturer Related Removal. R - Retread / Repair Related Removal.
Comments	Any Additional Comments That May Be Useful.